

## Linear Motor Coils Assembly And Manufacturing Method Thereof

**Field of the Invention**

5           The present invention relates to a linear motor for generating linear movement. More particularly, the present invention relates to a linear motor coil assembly having a plurality of coils arranged in a line in the direction of linear motion.

**Background Art**

10           Machine tools are known that use a linear motor to cause a table to move linearly at high speed and to position the table with high precision. Recently, linear motors have become more widely used. Such motors do not require conveying means such as a feed screw. A linear motor may be used in a machine tool when it is needed to generate a large thrust, and where more compact structures are needed.

15           However, because of their compact size, linear motors generate more heat than rotary motors. The temperature rise associated with a linear motor may limit its rated thrust, and lower its mechanical positioning accuracy. In many cases, linear motors are encapsulated in a cover in order to prevent magnetic dust from infiltrating into the linear motor. Because of this encapsulation, insufficient natural cooling of the

20           linear motor may result, making effective cooling of the linear motor an important consideration.

          Japanese Laid-Open Patent Application 63-18956 discloses a cooling apparatus for a linear motor. The motor is equipped with a cooling tube at the bottom of a groove formed between adjoining pole teeth. This linear motor cooling

25           tube will now be described in detail below with reference to Fig. 9, Fig. 10 and Fig.

11. A plurality of permanent magnets **3** having alternating magnetic poles are fixed in a line on the lower surface of a carrier **2** in the direction of movement. A fixed armature is made up of a plurality of T-shaped pole teeth **4**, a base **5** connecting the pole teeth, and a coil **7** wound around the teeth **4**. As clearly shown in Fig. 9, cooling tubes **8** are provided, one each at the bottom of grooves **6** formed by adjoining pole teeth **4**. The cooling tubes **8** comprise, for example, a tube **8A** which meanders around the grooves **6**, as shown in Fig. 10. A coolant, in gas or liquid form, circulates in the pipe **8A**. As shown in Fig. 11, the cooling tubes **8**, may comprise stair-shaped pipes **8B**. The pipes **8B** are equipped with headers **8a** and **8b** which extend parallel to a moving direction, opposite with respect to the base **5**, and a bridging section **8c**, bridging the headers **8a** and **8b**. The coolant is introduced from one end of the header **8a**, passes through the bridging section **8c** and is discharged from one end of the header **8b**.

#### **Summary Of The Invention**

15           An object of the present invention is to provide a linear motor coil assembly that efficiently dissipates heat generated in the coil.

          Another object of the present invention is to provide a compact linear motor coil assembly.

20           Still another object of the present invention is to provide a simple method of manufacturing a linear motor coil assembly, having a high cooling efficiency.

          These and other objects are achieved by providing, according to the present invention, a linear motor coil assembly for developing linear motion. The coil assembly comprises a plurality of coils arranged in a line in the direction of movement, respective coil shafts being arranged perpendicular to the direction of movement, and a flat cooling pipe, having a cross section that is elongated in a

25

direction parallel to the coil shafts and having folds into which the coils can be engaged, the cooling pipe meandering inside the plurality of coils.

The flat cooling pipe preferably has a plurality of clearance holes for passing coolant formed in a direction parallel to the coil shafts.

5           Alternatively, the flat cooling pipe for passing coolant may be formed by aligning and attaching a plurality of round pipes in a direction parallel to the coil shafts.

The flat cooling tube preferably has interleaved folds at least equal in number to the number of coils.

10           The linear motor coil assembly may also include cores, divided for each coil, around which the coils are wound.

According to the present invention, there is also provided a method of manufacturing a linear motor assembly for developing linear motion, comprising the steps of providing cores divided for each magnetic pole, winding coils around the  
15       respective cores, providing a flat cooling pipe having interleaved folds, at least equal in number to the number of coils, into which the coils may be engaged, fitting the core into the folds, and arranging the cores in a line on a base plate.

Other objects and novel features will become apparent upon consideration of the following description.

## 20   **Brief Description Of The Drawings**

Fig. 1 is a front elevation depicting an embodiment of a linear motor coil assembly of the present invention;

Fig. 2 is a plan view depicting the coil assembly of Fig. 1;

Fig. 3 is a cross sectional drawing showing a coil and a cooling tube in

25   Fig. 1 in magnified form;

Fig. 4 is a cross sectional drawing showing conveyance of the heat generated in the coils to the cooling tube;

Fig. 5 is a perspective view depicting another embodiment of the cooling tube in Fig. 1;

5 Fig. 6A, Fig. 6B, Fig. 6C and Fig. 6D are plan drawings depicting a method of manufacturing a linear motor coil assembly;

Fig. 7 is a perspective view of a coil assembly viewed in the direction of arrow B in Fig. 6;

Fig. 8 is a perspective view showing the coil assembly of Fig. 1 covered  
10 by an insulating resin;

Fig. 9 is a plan view of a linear motor according to the background art;

Fig. 10 is a cross sectional view of one example of a cooling tube taken along line A - A in Fig. 9; and

Fig. 11 is a cross sectional view of another example of a cooling tube  
15 taken along line A - A in Fig. 9.

#### **Preferred Embodiment of The Invention**

A linear motor coil assembly according to an embodiment of the present invention will now be described with reference to Fig. 1, Fig. 2, Fig. 3 and Fig. 4.

A linear motor coil assembly **12** for developing motion in the direction of  
20 a horizontal linear axis X has a base plate **11**, cores **13** having coils **14** mounted thereon. The coil assembly **12** may constitute either a mover or a stator. Reference numeral **G1** in Fig. 1 represents a gap formed between a stator and a mover. The base plate **11** has a horizontal upper surface. The cores **13** divided for each magnetic pole and aligned in a line in the direction of the linear axis X are attached to the  
25 upper surface of the base plate **11** using screws **19**. A plurality of holes **18** for the

screws **19** are formed in the base plate. The cores **13** are preferably formed by laminating silicon-steel plates and welding or gluing them together. As illustrated in Fig. 2, the cores **13** extend parallel to each other in a horizontal direction Y perpendicular to the linear axis X. As illustrated in Fig. 3, a gap **G2** is formed between pole faces **13a** of adjoining cores **13**. In order to make the gap **G2** as small as possible, the pole faces **13a** of the cores **13** protrude in the direction of the linear axis X. The size of the gap **G2** is preferably maintained at a value about double the gap **G1**. A small gap **G2** reduces undesirable torque ripple. A yoke section **13b** is formed connecting adjoining cores **13**, and holes **13c** for screws **19** are formed in the yoke section **13b**. In the illustrated embodiment, a set of insulators **15**, for insulating the coils **14**, are inserted into the cores **13**. The coils **14** are wound around respective cores **13** via insulators **15**, preferably without overlapping. The coil axes Z are parallel to each other, and perpendicular to the linear axis X. The insulators **15** may, for example, be made of compact liquid crystal polymer resin capable of being thinly formed and having high thermal conductivity. As illustrated in Fig. 2, the insulators **15** have a generally U-shaped horizontal cross section, and a set of insulators are fit onto each core **13**. Tapered insulators **16** for preventing damage to the finish, e.g., enamel paint, of the coils **14** are preferably wrapped around the outside of the coils **14**. A flat cooling tube **20**, arranged so as to meander around the inside of the coils **14**, is arranged in the direction of the linear axis X. The cooling tube **20** is preferably made of extruded aluminum. The cooling tube **20** is preferably glued to the coils **14**, and the insulators **16** improve adherence between the coils **14** and the cooling tube **20**. As illustrated in Fig. 3, the cooling tube **20** has a cross section elongated parallel to the coil axes Z, and is arranged higher than the height H1 of the yoke section **13b**. The length of the elongated cross section is preferably

the same as, or slightly larger than, the length L of the coils **14** in the axial direction. As a result, the cooling tube **20** is glued to almost the entire outer surface of the coils **14**, which are a source of heat. A plurality of holes **25**, through which coolant flows, are formed in the cooling tube **20** in a direction parallel to the coil axes. Preferably,

5 the cooling tube **20** does not have any branches, which means that no stagnation occurs in the flow of coolant. As shown by the arrows in Fig. 4, heat generated in the coils **14** which is conducted to an outer side is directly cooled by coolant inside the cooling tube **20**. Heat conducted from the coils **14** to the cores **13** is transferred through pole surfaces **13a** close to the cooling tube **20** and the yoke section **13b** to

10 the cooling tube **20**.

Fig. 5 illustrates another example of the cooling tube **20**. The cooling tube **20** of Fig. 5 has a plurality of round copper pipes arranged parallel to the coil axes Z. Adjoining copper pipes **26** are preferably joined by brazing. The two ends **20a** and **20b** of the cooling tube **20** are connected to respective manifolds **21** and **22**,

15 preferably by welding.

A method of manufacturing a coil assembly according to the present invention will now be described in detail below with reference to Fig. 6A, Fig. 6B, Fig. 6C, Fig. 6D.

As shown in the exemplary embodiment of Fig. 6A, cores at two

20 locations, corresponding to the head and tail of a row of cores are temporarily attached to an upper surface of a base plate **11** using screws **19**. In the illustrated embodiment, a row of cores is made up of nine cores **13**. The coils **14** are wound around the cores **13** using a coil winding machine. Since the cores are divided for each coil **14**, winding of the coils **14** is simple. As shown in Fig. 6B, a flat cooling

25 tube **20** having interleaved folds at least equal in number to the number of coils **14**,

is provided in the illustrated embodiment a flat cooling tube **20** having nine interleaved folds is provided. The folds of the cooling tube **20** are formed to correspond to the outline of the coils **14**, so that the coils **14** fit into the folds. The two ends of the cooling tube **20** are fixed preferably by welding, to elongated holes formed in manifolds **21** and **22**. The cooling tube **20** is moved horizontally, and the folds of the cooling tube **20** fit into two coils **14** on the base plate **11**. In the illustrated embodiment, three cores **13** are then moved horizontally, and inserted into folds of the cooling tube **20**. Then, as shown in Fig. 6C, an odd number, in this case five, cores of the row of cores are arranged on the upper plane of the base plate. Since the cores are inserted in the direction in which the coils are wound, damage to the coils is unlikely. An even number of cores of the core row, in this case four, are then moved horizontally and inserted into folds of the cooling tube **20**. One of the manifolds **21** is fixed to one end of the base plate **11**. All of the cores **13** are then fixed to the base plate **11** using screws **19**. As shown in Fig. 6D and Fig. 7, a cylindrical member **23** is vertically attached to the other end of the base plate **11**. The cooling tube **20** remaining at the other end of the base plate **11** is bent around the center of the cylindrical member **23**. Then, the other manifold **22** is fixed to one end of the base plate **11**.

After lead wires of the coils **14** have been located on the outer side of the base plate, the coil assembly **12** may be covered with a box-shaped frame. The frame is filled with insulating resin until the pole faces **13a** of the cores **13** are covered. The fixed resin compact may then be finished to the specified dimensions so as to expose the pole faces **13a**.

Fig. 8 depicts the coil assembly covered with the insulating resin as described above. Where the insulating resin sufficiently permeates into the coil

assembly 12, there is no need for the insulators 16.

The illustrated embodiment has been selected simply to describe the essence and practical application of the present invention, the scope of which is defined solely by the appended claims.

TO/240 6040360